

Product	Optocouplers								
Applicant	Everlight Electronics Co., Ltd. No.6-8, Zhonghua Rd., Shulin Dist., New Taipei City, Taipei 23860 Taiwan								
Manufacturer	Everlight Electronics Co., Ltd. No.6-8, Zhonghua Rd., Shulin Dist., New Taipei City, Taipei 23860 Taiwan								
Factory	Everlight Electronic (China) Co., Ltd. No. 2135 Zhong Shan North Rd., Wujiang Economy Development Zone China (Yun Xi Area), Songling Town, Wujiang City, Jiang Su PRC								
Ratings	250Vrms								
Trade mark	EVERLIGHT								
Model / Type Ref.	EL817./EL816./EL819./EL829./EL826./EL827./ EL717./4N25./4N26./4N27./4N28./4N35./4N36./4N37./4N38./MCT2./MCT2E./ MCT210./CNY17-1./CNY17-2./CNY17-3./CNY17-4./MOC8111./MOC8112./ MOC8113./H11A1./H11A2./H11A3./H11A4./H11A5./TIL111./TIL117./CNX35U./								
Principal characteristics	Optocoupler. Minimum external creepage distance is measured to 7.7mm, minimum internal creepage distance is measured to 6.0mm and minimum distance through insulation is measured to 0.5mm. Tested for reinforced insulation. Thermal cycling test, 10 cycles. Each cycle: 68h in 110 degree C, 1h in 25 degree C, 2h in 0 degree C and 1h in 25 degree C. After the cycling test a humidity test for 48h in 93% relative humidity. Electric strength test between input and output 4800Vac/1 minute. The symbol "." in type designation may be blank, A~Z or numbers, and denote different pin shape. Maximum operating temperature: 110°C. Tested for 5000m.								
A sample of the product was tested and found to be in conformity with	<table><tr><td>TRON</td><td>EN 60065:2014 IEC 60065:2001, IEC 60065:2001/AMD1:2005, IEC 60065:2001/AMD2:2010</td></tr><tr><td>OFF</td><td>EN 60950-1:2006;A11;A1;A12;A2 EN 62368-1:2014 IEC 60950-1:2005, IEC 60950-1:2005/AMD1:2009, IEC 60950-1:2005/AMD2:2013 IEC 62368-1:2014</td></tr><tr><td>LITE</td><td>EN 61347-1:2015 IEC 61347-1:2015</td></tr><tr><td>HOUS</td><td>EN 60335-1:2012;A11 IEC 60335-1:2010, IEC 60335-1:2010/AMD1:2013</td></tr></table>	TRON	EN 60065:2014 IEC 60065:2001, IEC 60065:2001/AMD1:2005, IEC 60065:2001/AMD2:2010	OFF	EN 60950-1:2006;A11;A1;A12;A2 EN 62368-1:2014 IEC 60950-1:2005, IEC 60950-1:2005/AMD1:2009, IEC 60950-1:2005/AMD2:2013 IEC 62368-1:2014	LITE	EN 61347-1:2015 IEC 61347-1:2015	HOUS	EN 60335-1:2012;A11 IEC 60335-1:2010, IEC 60335-1:2010/AMD1:2013
TRON	EN 60065:2014 IEC 60065:2001, IEC 60065:2001/AMD1:2005, IEC 60065:2001/AMD2:2010								
OFF	EN 60950-1:2006;A11;A1;A12;A2 EN 62368-1:2014 IEC 60950-1:2005, IEC 60950-1:2005/AMD1:2009, IEC 60950-1:2005/AMD2:2013 IEC 62368-1:2014								
LITE	EN 61347-1:2015 IEC 61347-1:2015								
HOUS	EN 60335-1:2012;A11 IEC 60335-1:2010, IEC 60335-1:2010/AMD1:2013								

Date of issue 20-07-2017

Juan Z. Kleppenes  
Certification Department**Nemko AS**Gaustadalléen 30, P.O. Box 73 Blindern, 0314 Oslo, Norway  
TEL +47 22 96 03 30 FAX +47 22 96 05 50 EMAIL info@nemko.com  
ENTERPRISE NUMBER NO974404532

Replaces	This certificate replaces previous certificate No. P15219385/A2, due to adding new models and updating existing standard with new addition
Validity	This certificate documents conformity with the standards shown, and also applies as license for use of Nemkos name and certification mark. The certificate and license is valid as long as the applicable conditions are complied with, and provided that any changes to the product are notified to Nemko for acceptance prior to implementation. New standards or amendments to the standards may imply that the product design must be updated and/or that re-testing and re-certification is necessary.
Additional information	
Additional model(s)	(28) See page 3

Date of issue 20-07-2017



Juan Z. Kleppenes  
Certification Department

**Nemko AS**

Gaustadalléen 30, P.O. Box 73 Blindern, 0314 Oslo, Norway  
TEL +47 22 96 03 30 FAX +47 22 96 05 50 EMAIL info@nemko.com  
ENTERPRISE NUMBER NO974404532

Additional model(s)

Product

Optocouplers

Pos. No

1

Model / Type Ref.

EL2200./EL2212./EL2231./EL2201./EL2202./EL2219./EL2211./ EL2232.

Trade mark (if different from page 1)

Rating

250Vrms

Principal characteristics

High Speed Optocoupler. Minimum external creepage distance is measured to 8.2mm, minimum internal creepage distance is measured to 5.1mm and minimum distance through insulation is measured to 0.5mm. Tested for reinforced insulation. Thermal cycling test, 10 cycles. Each cycle: 68h in 100 degree C, 1h in 25degree C, 2h in 0 degree C and 1h in 25 degree C. After the cycling test a humidity test for 48h in 93% relative humidity. Electric strength tests, between input and output 4800Vac/1 minute. The symbol "." in type designation may be blank, A~Z or numbers, and denote different pin shape. Maximum operating temperature: 100°C

Product

Optocouplers

Pos. No

2

Model / Type Ref.

ELR3602./ELR3603./ELR2602./ELR2603./ELR1602./ELR1603./ELR3502./  
ELR3503./ELR2502./ELR2503./ELR1502./ELR1503./ELR0223./ELR1223./  
ELR2223./ELR3223.

Trade mark (if different from page 1)

Rating

250Vrms

Principal characteristics

Power Triac Optocoupler. Minimum external creepage distance is measured to 8.2mm, minimum internal creepage distance is measured to 5.1mm and minimum distance through insulation is measured to 0.5mm. Tested for reinforced insulation. Thermal cycling test, 10 cycles. Each cycle: 68h in 100 degree C, 1h in 25degree C, 2h in 0 degree C and 1h in 25 degree C. After the cycling test a humidity test for 48h in 93% relative humidity. Electric strength tests, between input and output 4800Vac/1 minute. The symbol "." in type designation may be blank, A~Z or numbers, and denote different pin shape. Maximum operating temperature: 100°C.

Date of issue 20-07-2017



Juan Z. Kleppenes

Certification Department

**Nemko AS**

Gaustadalléen 30, P.O. Box 73 Blindern, 0314 Oslo, Norway

TEL +47 22 96 03 30 FAX +47 22 96 05 50 EMAIL info@nemko.com

ENTERPRISE NUMBER NO974404532

Product	Optocouplers
Pos. No	3
Model / Type Ref.	EL847./EL844./EL845.
Trade mark (if different from page 1)	
Rating	250Vrms
Principal characteristics	Optocoupler. Minimum external creepage distance is measured to 8.0mm, minimum internal creepage distance is measured to 5.1mm and minimum distance through insulation is measured to 0.5mm. Tested for reinforced insulation. Thermal cycling test, 10 cycles. Each cycle: 68h in 110 degree C, 1h in 25 degree C, 2h in 0 degree C and 1h in 25 degree C. After the cycling test a humidity test for 48h in 93% relative humidity. Electric strength tests, between input and output 4800Vac/1 minute. The symbol "." in type designation may be A to Z, numbers or blank, denote different pin shape. Maximum operating temperature: 110°C
Product	Optocouplers
Pos. No	4
Model / Type Ref.	EL2801./EL354./EL355./EL356./EL357./EL359./EL121./EL124./EL2701./EL2705./EL357N./EL356N./EL121N./EL124N./EL2701N./EL354N./EL2705N./EL3H7./EL281./EL3H4./EL280./EL3H71./ELM301X./ELM302X./ELM305X./ELM307X./ELM303X./ELM304X./ELM306X./ELM308X.
Trade mark (if different from page 1)	
Rating	250Vrms
Principal characteristics	Optocoupler. Minimum external creepage distance is measured to 5.0mm, minimum internal creepage distance is measured to 4.0mm and minimum distance through insulation is measured to 0.4mm. Tested for reinforced insulation. Thermal cycling test, 10 cycles. Each cycle: 68h in 110 degree C, 1h in 25 degree C, 2h in 0 degree C and 1h in 25 degree C. After the cycling test a humidity test for 48h in 93% relative humidity. Electric strength test between input and output 4800Vac/1 minute. The symbol "." in type designation may be blank, A~Z or numbers, and denote different pin shape. Maximum operating temperature: 110°C. The symbol "X" in type denotes X = Part no. (0,1,2,3,4).

Date of issue 20-07-2017



Juan Z. Kleppenes  
Certification Department

**Nemko AS**  
Gaustadalléen 30, P.O. Box 73 Blindern, 0314 Oslo, Norway  
TEL +47 22 96 03 30 FAX +47 22 96 05 50 EMAIL info@nemko.com  
ENTERPRISE NUMBER NO974404532

Product	Optocouplers
Pos. No	5
Model / Type Ref.	EL815./ EL814./EL824./ EL825.
Trade mark (if different from page 1)	
Rating	250Vrms
Principal characteristics	Optocoupler. Minimum external creepage distance is measured to 7.9mm, minimum internal creepage distance is measured to 6.0mm and minimum distance through insulation is measured to 0.5mm. Tested for reinforced insulation. Thermal cycling test, 10 cycles. Each cycle: 68h in 110 degree C, 1h in 25degree C, 2h in 0 degree C and 1h in 25 degree C. After the cycling test a humidity test for 48h in 93% relative humidity. Electric strength test between input and output 4800Vac/1 minute. The symbol "." in type designation may be blank, A~Z or numbers, and denote different pin shape. Maximum operating temperature: 110°C
Product	Optocouplers
Pos. No	6
Model / Type Ref.	EL617./CNY75G./CQY80.G/K233.G/TCDT110.G/TCDT111.G/TCDT112.G/HS817.G/TCET110.G/TCET111.G/ TCET120.G
Trade mark (if different from page 1)	
Rating	250Vrms
Principal characteristics	Optocoupler. Minimum external creepage distance is measured to 8.0mm, minimum internal creepage distance is measured to 6.0mm and minimum distance through insulation is measured to 0.5mm. Tested for reinforced insulation. Thermal cycling test, 10 cycles. Each cycle: 68h in 110 degree C, 1h in 25 degree C, 2h in 0 degree C and 1h in 25 degree C. After the cycling test a humidity test for 48h in 93% relative humidity. Electric strength test between input and output 4800Vac/1 minute. The symbol "." in type designation may be blank, A~Z or numbers, and denote different pin shape. Maximum operating temperature: 110°C.

Date of issue 20-07-2017



Juan Z. Kleppenes  
Certification Department

Product	Optocouplers
Pos. No	7
Model / Type Ref.	EL205./EL206./EL207./EL208./EL211./EL212./EL213./EL215./EL216./EL217./ ELD207./ELD208./ELD213./ELD217./ELD205./ELD206./ELD211.
Trade mark (if different from page 1)	
Rating	250Vrms
Principal characteristics	Optocoupler. Minimum external creepage distance is measured to 4.4mm, minimum internal creepage distance is measured to 3.5mm and minimum distance through insulation is measured to 0.4mm. Tested for basic and supplementary insulation. Thermal cycling test, 10 cycles. Each cycle: 68h in 110 degree C, 1h in 25 degree C, 2h in 0 degree C and 1h in 25 degree C. After the cycling test a humidity test for 48h in 93% relative humidity. Electric strength test between input and output 2400Vac/1 minute. The symbol "." in type designation may be blank, A~Z or numbers, and denote different pin shape. Maximum operating temperature: 110°C.
Product	Optocouplers
Pos. No	8
Model / Type Ref.	6N135./6N136./6N137./6N138./6N139./EL2502./EL250L./EL2503./EL4502./ EL4503./EL2530./EL253L./EL2531./EL4534./EL2730./EL2731./EL2601./ EL260L./EL2611./EL261A./EL261N./EL2630./EL263L./EL263A./EL263N./ EL2631./EL4661./EL4504.
Trade mark (if different from page 1)	
Rating	250Vrms
Principal characteristics	High Speed Optocoupler. Minimum external creepage distance is measured to 8.0mm, minimum internal creepage distance is measured to 5.0mm and minimum distance through insulation is measured to 0.5mm. Tested for reinforced insulation. Thermal cycling test, 10 cycles. Each cycle: 68h in 100 degree C, 1h in 25 degree C, 2h in 0 degree C and 1h in 25 degree C. After the cycling test a humidity test for 48h in 93% relative humidity. Electric strength test between input and output 4800Vac/1 minute. The symbol "." in type designation may be blank, A~Z or numbers, and denote different pin shape. Maximum operating temperature: 100°C

Date of issue 20-07-2017



Juan Z. Kleppenes  
Certification Department

**Nemko AS**

Gaustadalléen 30, P.O. Box 73 Blindern, 0314 Oslo, Norway  
TEL +47 22 96 03 30 FAX +47 22 96 05 50 EMAIL info@nemko.com  
ENTERPRISE NUMBER NO974404532

Product	Optocouplers
Pos. No	9
Model / Type Ref.	EL0500./EL0501./EL0452./EL0453./EL0454./EL0600./EL0601./EL0611./ EL0700./EL050L./EL060L./EL0701./EL061A./EL061N./EL0551./EL0530./ EL0531./EL0533./EL063X./EL0661./EL0730./EL0731./EL053L.
Trade mark (if different from page 1)	
Rating	250Vrms
Principal characteristics	High Speed Optocoupler. Minimum external creepage distance is measured to 4.4mm, minimum internal creepage distance is measured to 3.5mm and minimum distance through insulation is measured to 0.4mm. Tested for basic and supplementary insulation. Thermal cycling test, 10 cycles. Each cycle: 68h in 100 degree C, 1h in 25degree C, 2h in 0 degree C and 1h in 25 degree C. After the cycling test a humidity test for 48h in 93% relative humidity. Electric strength test between input and output 2400Vac/1 minute. The symbol "." in type designation may be blank, A~Z or numbers, and denote different pin shape. Maximum operating temperature: 100°C. The symbol "X" in type denotes X = Part no. (0,1,L,A,N).
Product	Optocouplers
Pos. No	10
Model / Type Ref.	EL101X./ EL357L./ EL355L./ EL354L./ EL111X./ EL161X./ EL151X./EL101L.
Trade mark (if different from page 1)	
Rating	250Vrms
Principal characteristics	Optocoupler. Minimum external creepage distance is measured to 8.1mm, minimum internal creepage distance is measured to 5.2mm and minimum distance through insulation is measured to 0.4mm. Tested for reinforced insulation. Thermal cycling test, 10 cycles. Each cycle: 68h in 110 degree C, 1h in 25degree C, 2h in 0 degree C and 1h in 25 degree C. After the cycling test a humidity test for 48h in 93% relative humidity. Electric strength test between input and output 4800Vac/1 minute. The symbol "." in type designation may be blank, A~Z or numbers, and denote different pin shape. Maximum operating temperature: 110°C. The symbol "X" in type denotes X = Part no. (0,1,2,3,4,5,6,7,8,9). Tested for 5000m.

Date of issue 20-07-2017



Juan Z. Kleppenes  
Certification Department

**Nemko AS**  
Gaustadalléen 30, P.O. Box 73 Blindern, 0314 Oslo, Norway  
TEL +47 22 96 03 30 FAX +47 22 96 05 50 EMAIL info@nemko.com  
ENTERPRISE NUMBER NO974404532

Product	Optocouplers
Pos. No	11
Model / Type Ref.	EL806A./ EL810A./ EL820A./ EL825A./ EL835A./ EL840A./ EL860A./ EL406A./ EL410A./ EL420A./ EL425A./ EL435A./ EL440A./ EL460A./ EL606A./ EL610A./ EL620A./ EL625A./ EL635A./ EL640A./ EL660A.
Trade mark (if different from page 1)	
Rating	250Vrms
Principal characteristics	Solid State Relay. Minimum external creepage distance is measured to 7.7mm, minimum internal creepage distance is measured to 6.0mm and minimum distance through insulation is measured to 0.5mm. Tested for reinforced insulation. Maximum operating temperature: 85°C. Thermal cycling test, 10 cycles. Each cycle: 68h in 85 degree C, 1h in 25 degree C, 2h in 0 degree C and 1h in 25 degree C. After the cycling test a humidity test for 48h in 93% relative humidity. Electric strength test between input and output 4800Vac/1 minute. The symbol "." in type designation may be blank, A~Z or numbers, and denote different pin shape.
Product	Optocouplers
Pos. No	12
Model / Type Ref.	EL451./EL452./EL3H7L./ EL351./ EL352./ EL3571N./ EL357NL.
Trade mark (if different from page 1)	
Rating	250Vrms
Principal characteristics	Optocoupler. Minimum external creepage distance is measured to 5.0mm, minimum internal creepage distance is measured to 4.0mm and minimum distance through insulation is measured to 0.4mm. Tested for reinforced insulation. Thermal cycling test, 10 cycles. Each cycle: 68h in 110 degree C, 1h in 25 degree C, 2h in 0 degree C and 1h in 25 degree C. After the cycling test a humidity test for 48h in 93% relative humidity. Electric strength test between input and output 4800Vac/1 minute. The symbol "." in type designation may be blank, A~Z or numbers, and denote different pin shape. Maximum operating temperature: 110°C. The symbol "X" in type denotes X = Part no. (0,1,2,3,4).

Date of issue 20-07-2017



Juan Z. Kleppenes  
Certification Department

**Nemko AS**  
Gaustadalléen 30, P.O. Box 73 Blindern, 0314 Oslo, Norway  
TEL +47 22 96 03 30 FAX +47 22 96 05 50 EMAIL info@nemko.com  
ENTERPRISE NUMBER NO974404532



Product	Optocouplers
Pos. No	13
Model / Type Ref.	H11L3./H11D1./H11D2./H11D3./H11D4./H11G1./H11G2./EL371./ EL725./4N50./4N51./4N52./4N53./4N54./4N55./4N56./4N57./4N58./4N59./ EL852./EL851./H11G3.
Trade mark (if different from page 1)	
Rating	250Vrms
Principal characteristics	Optocoupler. Minimum external creepage distance is measured to 7.7mm, minimum internal creepage distance is measured to 5.5mm and minimum distance through insulation is measured to 0.5mm. Tested for reinforced insulation. Thermal cycling test, 10 cycles. Each cycle: 68h in 100 degree C, 1h in 25degree C, 2h in 0 degree C and 1h in 25 degree C. After the cycling test a humidity test for 48h in 93% relative humidity. Electric strength test between input and output 4800Vac/1 minute. The symbol "." in type designation may be blank, A~Z or numbers, and denote different pin shape. Maximum operating temperature: 100°C. The symbol "X" in type denotes X = Part no. (0,1,2,3,4)
Product	Optocouplers
Pos. No	14
Model / Type Ref.	CNX36U./CNX38U./CNX39U./SL5500./SL5501./SL5504./SL5511./ MOC8100./MOC8101./MOC8102./MOC8103./MOC8104./MOC8105./ MOC8106./MOC8107./MOC8108./EL9001./CNY17F-1./CNY17F-2./ CNY17F-3./CNY17F-4./H11AA1./H11AA2./H11AA3./H11AA4./HS817./ K817P./TCET110.
Trade mark (if different from page 1)	
Rating	250Vrms
Principal characteristics	Optocoupler. Minimum external creepage distance is measured to 7.7mm, minimum internal creepage distance is measured to 6.0mm and minimum distance through insulation is measured to 0.5mm. Tested for reinforced insulation. Thermal cycling test, 10 cycles. Each cycle: 68h in 110 degree C, 1h in 25 degree C, 2h in 0 degree C and 1h in 25 degree C. After the cycling test a humidity test for 48h in 93% relative humidity. Electric strength test between input and output 4800Vac/1 minute. The symbol "." in type designation may be blank, A~Z or numbers, and denote different pin shape. Maximum operating temperature: 110°C. Tested for 5000m.

Date of issue 20-07-2017



Juan Z. Kleppenes  
Certification Department

**Nemko AS**

Gaustadalléen 30, P.O. Box 73 Blindern, 0314 Oslo, Norway  
TEL +47 22 96 03 30 FAX +47 22 96 05 50 EMAIL info@nemko.com  
ENTERPRISE NUMBER NO974404532

Product Optocouplers  
Pos. No 15  
Model / Type Ref. TCET111./TCET120./VO610A./VO615A./CNY17G./CNY75./CQY80./K233./  
TCDT110./TCDT111./TCDT112./EL2501./EL2561./EL8171./CNY171-1./  
CNY171-2./CNY171-3./CNY171-4./CNY17F1-1./CNY17F1-2./CNY17F1-3./  
CNY17F1-4./EL610./EL817L.

Trade mark (if different from page 1)  
Rating 250Vrms  
Principal characteristics Optocoupler. Minimum external creepage distance is measured to 7.7mm, minimum internal creepage distance is measured to 6.0mm and minimum distance through insulation is measured to 0.5mm. Tested for reinforced insulation. Thermal cycling test, 10 cycles. Each cycle: 68h in 110 degree C, 1h in 25 degree C, 2h in 0 degree C and 1h in 25 degree C. After the cycling test a humidity test for 48h in 93% relative humidity. Electric strength test between input and output 4800Vac/1 minute. The symbol "." in type designation may be blank, A~Z or numbers, and denote different pin shape. Maximum operating temperature: 110°C. Tested for 5000m.

Product Optocouplers  
Pos. No 16  
Model / Type Ref. EL070L./EL071L./EL083L./ EL086L.  
Trade mark (if different from page 1)  
Rating 250Vrms  
Principal characteristics High Speed Optocoupler. Minimum external creepage distance is measured to 4.4mm, minimum internal creepage distance is measured to 3.5mm and minimum distance through insulation is measured to 0.4mm. Tested for basic and supplementary insulation. Thermal cycling test, 10 cycles. Each cycle: 68h in 100 degree C, 1h in 25degree C, 2h in 0 degree C and 1h in 25 degree C. After the cycling test a humidity test for 48h in 93% relative humidity. Electric strength test between input and output 2400Vac/1 minute. The symbol "." in type designation may be blank, A~Z or numbers, and denote different pin shape. Maximum operating temperature: 100°C. The symbol "X" in type denotes X = Part no. (0,1,L,A,N)

Date of issue 20-07-2017



Juan Z. Kleppenes  
Certification Department

**Nemko AS**  
Gaustadalléen 30, P.O. Box 73 Blindern, 0314 Oslo, Norway  
TEL +47 22 96 03 30 FAX +47 22 96 05 50 EMAIL info@nemko.com  
ENTERPRISE NUMBER NO974404532

Product	Optocouplers
Pos. No	17
Model / Type Ref.	ELS500./ELS501./ELS511./ELS050L./ELS051L./ELS052L./ELS600./ELS601./ELS611./ELS060L./ELS061L./ELS062L.
Trade mark (if different from page 1)	
Rating	250Vrms
Principal characteristics	High Speed Optocoupler . Minimum external creepage distance is measured to 8.4mm, minimum internal creepage distance is measured to 5.56mm and minimum distance through insulation is measured to 0.4mm. Tested for reinforced insulation. Thermal cycling test, 10 cycles. Each cycle: 68h in 100 degree C, 1h in 25degree C, 2h in 0 degree C and 1h in 25 degree C. After the cycling test a humidity test for 48h in 93% relative humidity. Electric strength test between input and output 4800Vac/1 minute.The symbol “.” in type designation may be blank, A~Z or numbers, and denote different pin shape. Maximum operating temperature: 100°C
Product	Optocouplers
Pos. No	18
Model / Type Ref.	ELM440A./ELM460A./ELM640A./ELM660A./ELM840A./ELM860A.
Trade mark (if different from page 1)	
Rating	250Vrms
Principal characteristics	Solid State Relay. Minimum external creepage distance is measured to 5.7mm, minimum internal creepage distance is measured to 4.31mm and minimum distance through insulation is measured to 0.3mm. Tested for basic and supplementary insulation. Thermal cycling test, 10 cycles. Each cycle: 68h in 100 degree C, 1h in 25 degree C, 2h in 0 degree C and 1h in 25 degree C. After the cycling test a humidity test for 48h in 93% relative humidity. Electric strength test between input and output 4800Vac/1 minute. The symbol “.” in type designation may be blank, A~Z or numbers, and denote different pin shape. Maximum operating temperature: 100°C
Product	Optocouplers
Pos. No	19
Model / Type Ref.	EL101XH.
Trade mark (if different from page 1)	
Rating	250Vrms
Principal characteristics	Optocoupler. Minimum external creepage distance is measured to 8.1mm, minimum internal creepage distance is measured to 5.2mm and minimum distance through insulation is measured to 0.4mm. Tested for reinforced insulation. Thermal cycling test, 10 cycles. Each cycle: 68h in 125 degree C, 1h in 25degree C, 2h in 0 degree C and 1h in 25 degree C. After the cycling test a humidity test for 48h in 93% relative humidity. Electric strength test between input and output 4800Vac/1 minute. Maximum operating temperature: 125°C. The symbol “X” in type denotes X = Part no. (0,1,2,3,4,5,6,7,8,9)

Date of issue 20-07-2017



Juan Z. Kleppenes

Certification Department

**Nemko AS**

Gaustadalléen 30, P.O. Box 73 Blindern, 0314 Oslo, Norway  
TEL +47 22 96 03 30 FAX +47 22 96 05 50 EMAIL info@nemko.com  
ENTERPRISE NUMBER NO974404532

Product	Optocouplers
Pos. No	20
Model / Type Ref.	EL357NH./EL3H7H.
Trade mark (if different from page 1)	
Rating	250Vrms
Principal characteristics	Optocoupler. Minimum external creepage distance is measured to 5.0mm, minimum internal creepage distance is measured to 4.0mm and minimum distance through insulation is measured to 0.4mm. Tested for reinforced insulation. Thermal cycling test, 10 cycles. Each cycle: 68h in 125 degree C, 1h in 25 degree C, 2h in 0 degree C and 1h in 25 degree C. After the cycling test a humidity test for 48h in 93% relative humidity. Electric strength test between input and output 4800Vac/1 minute. Maximum operating temperature: 125°C.
Product	Optocouplers
Pos. No	21
Model / Type Ref.	EL817H.
Trade mark (if different from page 1)	
Rating	250Vrms
Principal characteristics	Optocoupler. Minimum external creepage distance is measured to 7.7mm, minimum internal creepage distance is measured to 6.0mm and minimum distance through insulation is measured to 0.5mm. Tested for reinforced insulation. Thermal cycling test, 10 cycles. Each cycle: 68h in 125 degree C, 1h in 25 degree C, 2h in 0 degree C and 1h in 25 degree C. After the cycling test a humidity test for 48h in 93% relative humidity. Electric strength test between input and output 4800Vac/1 minute. Maximum operating temperature: 125°C

Date of issue 20-07-2017



Juan Z. Kleppenes  
Certification Department

**Nemko AS**  
Gaustadalléen 30, P.O. Box 73 Blindern, 0314 Oslo, Norway  
TEL +47 22 96 03 30 FAX +47 22 96 05 50 EMAIL info@nemko.com  
ENTERPRISE NUMBER NO974404532

Product Optocouplers  
Pos. No 22  
Model / Type Ref. ELT301X./ ELT302X./ ELT305X./ ELT303X./ ELT304X./ ELT306X./  
ELT308X./ ELT307X.  
Trade mark (if different from page 1)  
Rating 250Vrms  
Principal characteristics Triac Optocoupler. Minimum external creepage distance is measured to 7.7mm, minimum internal creepage distance is measured to 6.0mm and minimum distance through insulation is measured to 0.5mm. Tested for reinforced insulation. Maximum operating temperature: 110°C. Thermal cycling test, 10 cycles. Each cycle: 68h in 110 degree C, 1h in 25 degree C, 2h in 0 degree C and 1h in 25 degree C. After the cycling test a humidity test for 48h in 93% relative humidity. Electric strength test between input and output 4800Vac/1 minute. The symbol "X" in type denotes X = Part no. (0,1,2,3,4). The symbol "." in type designation may be blank, A~Z or numbers, and denote different pin shape.

Product Optocouplers  
Pos. No 23  
Model / Type Ref. ELW137./ ELW139./ ELW2601./ ELW2611./ ELW136./ ELW135./ ELW4502./  
ELW4503./ ELW138./ ELW260L./ ELW250L./ ELW4504./ELW2200./  
ELW2201./ ELW2202./ ELW2219./ ELW2211./ ELW2212.  
Trade mark (if different from page 1)  
Rating 250Vrms  
Principal characteristics High Speed Optocoupler. Minimum external creepage distance is measured to 11.85mm, minimum internal creepage distance is measured to 7.72mm and minimum distance through insulation is measured to 0.9mm. Tested for reinforced insulation. Maximum operating temperature: 100°C. Thermal cycling test, 10 cycles. Each cycle: 68h in 100 degree C, 1h in 25 degree C, 2h in 0 degree C and 1h in 25 degree C. After the cycling test a humidity test for 48h in 93% relative humidity. Electric strength test between input and output 4800Vac/1 minute. The symbol "." in type designation may be blank, A~Z or numbers, and denote different pin shape.

Date of issue 20-07-2017



Juan Z. Kleppenes  
Certification Department

**Nemko AS**  
Gaustadalléen 30, P.O. Box 73 Blindern, 0314 Oslo, Norway  
TEL +47 22 96 03 30 FAX +47 22 96 05 50 EMAIL info@nemko.com  
ENTERPRISE NUMBER NO974404532

Product	Optocouplers
Pos. No	24
Model / Type Ref.	EL3120./ EL3140./ EL3150./ EL3180./ EL3184.
Trade mark (if different from page 1)	
Rating	250Vrms
Principal characteristics	IGBT Gate Drive Optocoupler. Minimum external creepage distance is measured to 7.7mm, minimum internal creepage distance is measured to 6.0mm and minimum distance through insulation is measured to 0.5mm. Tested for reinforced insulation. Maximum operating temperature: 110°C. Thermal cycling test, 10 cycles. Each cycle: 68h in 110 degree C, 1h in 25 degree C, 2h in 0 degree C and 1h in 25 degree C. After the cycling test a humidity test for 48h in 93% relative humidity. Electric strength test between input and output 4800Vac/1 minute. The symbol "." in type designation may be blank, A~Z or numbers, and denote different pin shape
Product	Optocouplers
Pos. No	25
Model / Type Ref.	ELW3120./ ELW3140./ ELW3150./ ELW3180./ ELW3184.
Trade mark (if different from page 1)	
Rating	250Vrms
Principal characteristics	IGBT Gate Drive Optocoupler. Minimum external creepage distance is measured to 11.85mm, minimum internal creepage distance is measured to 7.72mm and minimum distance through insulation is measured to 0.9mm. Tested for reinforced insulation. Maximum operating temperature: 110°C. Thermal cycling test, 10 cycles. Each cycle: 68h in 110 degree C, 1h in 25 degree C, 2h in 0 degree C and 1h in 25 degree C. After the cycling test a humidity test for 48h in 93% relative humidity. Electric strength test between input and output 4800Vac/1 minute. The symbol "." in type designation may be blank, A~Z or numbers, and denote different pin shape

Date of issue 20-07-2017



Juan Z. Kleppenes  
Certification Department

Product Optocouplers  
Pos. No 26  
Model / Type Ref. ELD3H5./ ELD3H6./ ELD3H7./ ELD3H4./ ELQ3H4./ ELQ3H5./ ELQ3H7./ ELM314.  
Trade mark (if different from page 1)  
Rating 250Vrms  
Principal characteristics Optocoupler. Minimum external creepage distance is measured to 5.0mm, minimum internal creepage distance is measured to 4.0mm and minimum distance through insulation is measured to 0.4mm. Tested for reinforced insulation. Maximum operating temperature: 110°C. Thermal cycling test, 10 cycles. Each cycle: 68h in 110 degree C, 1h in 25 degree C, 2h in 0 degree C and 1h in 25 degree C. After the cycling test a humidity test for 48h in 93% relative humidity. Electric strength test between input and output 4800Vac/1 minute. The symbol "." in type designation may be blank, A~Z or numbers, and denote different pin shape

Product Optocouplers  
Pos. No 27  
Model / Type Ref. ELM452./ ELM453./ ELM600./ ELM601./ ELM611./ ELM452L./ ELM453L./ ELM600L./ ELM601L./ ELM611L./ELM454./ELM80L./ ELM81L.  
Trade mark (if different from page 1)  
Rating 250Vrms  
Principal characteristics High Speed Optocoupler. Minimum external creepage distance is measured to 5.0mm, minimum internal creepage distance is measured to 4.0mm and minimum distance through insulation is measured to 0.4mm. Tested for reinforced insulation. Maximum operating temperature: 100°C. Thermal cycling test, 10 cycles. Each cycle: 68h in 100 degree C, 1h in 25 degree C, 2h in 0 degree C and 1h in 25 degree C. After the cycling test a humidity test for 48h in 93% relative humidity. Electric strength test between input and output 4800Vac/1 minute. The symbol "." in type designation may be blank, A~Z or numbers, and denote different pin shape.

Date of issue 20-07-2017



Juan Z. Kleppenes  
Certification Department

**Nemko AS**  
Gaustadalléen 30, P.O. Box 73 Blindern, 0314 Oslo, Norway  
TEL +47 22 96 03 30 FAX +47 22 96 05 50 EMAIL info@nemko.com  
ENTERPRISE NUMBER NO974404532

Product	Optocouplers
Pos. No	28
Model / Type Ref.	ELD851./ELD852./4N29./4N30./4N31./4N32./4N33./H11B1./H11B2./H11B3./ H11B255./TIL113./MOC119./MOC8020./MOC8021./MOC8030./MOC8050./ MOC8080./EL301X./EL302X./EL305X./EL307X./EL303X./EL304X./EL306X./ EL308X./EL3161./EL3162./EL3163./H11L1./H11L2.
Trade mark (if different from page 1)	
Rating	250Vrms
Principal characteristics	Optocoupler. Minimum external creepage distance is measured to 7.7mm, minimum internal creepage distance is measured to 5.5mm and minimum distance through insulation is measured to 0.5mm. Tested for reinforced insulation. Thermal cycling test, 10 cycles. Each cycle: 68h in 100 degree C, 1h in 25degree C, 2h in 0 degree C and 1h in 25 degree C. After the cycling test a humidity test for 48h in 93% relative humidity. Electric strength test between input and output 4800Vac/1 minute. The symbol “.” in type designation may be blank, A~Z or numbers, and denote different pin shape. Maximum operating temperature: 100°C. The symbol “X” in type denotes X = Part no. (0,1,2,3,4).

Date of issue 20-07-2017



Juan Z. Kleppenes  
Certification Department

**Nemko AS**  
Gaustadalléen 30, P.O. Box 73 Blindern, 0314 Oslo, Norway  
TEL +47 22 96 03 30 FAX +47 22 96 05 50 EMAIL info@nemko.com  
ENTERPRISE NUMBER NO974404532